


P.T.O.
3000 r.p.m. - IP 23 2 poles Compound

GA AGRIPLUS 3-16

Technical data

		Three-phase 400V - 50Hz	Mono-phase 230V - 50Hz
Power	kVA	16	6.4
Active power	kW	12.8	5.12
Current	%	84.5	
Gear box	Ratio	1:6.9	
Driving power	kW	15.6	
Tractor power	HP	49	
P.T.O. speed	r.p.m.	430	
P.T.O. sizing Cardan	Nm	514	
	kW	29	
Dimensions (LxWxH)	Mm	929 x 640 x 915	
Weight	Kg	125	



Environmental conditions

Temperature	°C	25
Relative humidity	%	30
Maximum altitude	Mt	1000

EQUIPMENT

Alternator stabilized, high performance
 Gear box
 Raised chassis
 3-point-connection frame
 Control panel
 EC Protections

CONTROL PANEL ON BOARD

Instruments

Voltmeter
 Frequency meter

Protections

Single phase thermal protection
 4-pole magnetothermal switch
 Differential protection (Id=0,03A)
 IP65 cover

Outputs

1 CEE 400V (3P+N+E) 32A
 1 CEE 230V (2P+E) 16A



DOCUMENTATION

User and maintenance manual
 EC Declaration of Conformity

APPLICATIONS



AGRICULTURAL

