



**Generating Set
Gasoline - Snatch start up**

GE.ECHO 035 H BM AS



Technical data

Standard voltage	V	230
Power	kVA	3,5
Active power	kW	2,8
Speed	rpm	3000
Frequency	Hz	50
Current	A	12
Voltage accuracy	V	+/- 5%
Frequency accuracy	Hz	+/- 4%

General data

Start-up	Type	Pull starter
Sound pressure level @ 7 mt	dB(A)	69
Tank	Lt	3
Fuel consumption @ 4/4 load	Lt/H	0,9
Battery capacity (recommended)	Ah	-
Exhaust pipe diameter	Mm	30
Dimensions (LxWxH)	Mm	620 x 440 x 540
Dry weight	Kg	47

Engine

Brand	-	HONDA
Model	-	GX160
Cooling	Type	Air
Cycle	Type	4-stroke
Mechanical power	KWm	3,5
No cylinders / arrangement	-	1 - L
Brore x stroke	Mm	68 x 45
Displacement	Cm ³	163
Speed governor	Type	Mechanical

Alternator

Phases	-	1 + N
Degree of protection	-	IP21
Cooling	-	Forced air
Voltage regulator	Type	Condenser
Waveform distortion	%	<5

Environmental conditions

Temperature	°C	25
Relative humidity	%	30
Maximum altitude	Mt	1000



www.elcos.net - info@elcos.net

Elcos s.r.l. S.S. 234 Km 58.250 - 26023 Grumello Cremonese CR - Italy

EQUIPMENT

Protective cover
Forklift chassis with integrated anti-tip
Raised chassis
Easy start-up
Alternator stabilized, high performance
Handle for short displacements
Easy maintenance
Anti-vibrating mounting pads

CONTROL PANEL ON BOARD

n.1 CEE socket 16 A 2P + T
n.1 Schuko socket 16 A
Thermal circuit breaker
LED voltmeter
Hourcounter
Protection system to electrical separation



DOCUMENTATION

User and maintenance manual
EC Declaration of Conformity

OPTIONALS

Remote control Connector: O.G-CNA-01
Exhaust flexible pipe kit
Off road trailer kit

