



**Generating Set
Gasoline - Snatch start up**

GE.ECHO 070 H BT AS



Technical data

Standard voltage	V	230	400
Power	kVA	4*	7
Active power	kW	3,2	5,6
Speed	rpm	3000	
Frequency	Hz	50	
Current	A	14	10
Voltage accuracy	V	+/- 5%	
Frequency accuracy	Hz	+/- 4%	

* Not to be taken simultaneously with the three-phase power.

General data

Start-up	Type	Pull starter
Sound pressure level @ 7 mt	dbA	69
Tank	Lt	6
Fuel consumption @ 4/4 load	Lt/H	1,8
Battery capacity (recommended)	Ah	-
Exhaust pipe diameter	Mm	35
Dimensions (LxWxH)	Mm	760 x 520 x 620
Dry weight	Kg	91

Engine

Brand	-	HONDA
Model	-	GX390
Cooling	Type	Air
Cycle	Type	4-stroke
Mechanical power	KWm	8,1
No cylinders / arrangement	-	1 - In
Brore x stroke	Mm	88 x 64
Displacement	Cm ³	389
Speed governor	Type	Mechanical

Alternator

Phases	-	3 + N
Degree of protection	-	IP21
Cooling	-	Air forced
Voltage regulator	Type	Condenser
Waveform distortion	%	<5

Environmental conditions

Temperature	°C	25
Relative humidity	%	30
Maximum altitude	Mt	1000



www.elcos.net - info@elcos.net

Elcos s.r.l. S.S. 234 Km 58.250 - 26023 Grumello Cremonese CR - Italy

EQUIPMENT

Protective cover
Forklift chassis with integrated anti-tip
Raised chassis
Easy start-up
Alternator stabilized, high performance
Handle for short displacements
Easy maintenance
Anti-vibrating mounting pads

CONTROL PANEL ON BOARD

n.1 CEE socket 16 A 2P + T
n.1 CEE socket 16 A 3P + N + T
Thermal circuit breaker
LED voltmeter
Hourcounter
Magnetothermal
Protection system to electrical separation



DOCUMENTATION

User and maintenance manual
EC Declaration of Conformity

OPTIONALS

Remote control Connector: O.G-CNA-01
Exhaust flexible pipe kit
Off road trailer kit

